

# 5 Ton—208/240V Portable Air-Conditioning and Heating System



**MINI-SERIES**



Custom HVAC & Filtration • [jeff@wisperkool.com](mailto:jeff@wisperkool.com) • 9/2020

# Features and Specifications

The structural frame of the 5-ton wisperkool™ is fabricated from 11-gauge galvanized steel. All of the frame surfaces are protected with a high-performance anti-chip powder coat. The 3.5 ton is designed to cool and heat uninsulated spaces of 300–400 square feet.

Weight: 580 lbs.  
 Height: 45"  
 Length: 51"  
 Depth: 35.5"

## Refrigeration

- Refrigerant - 410A
- TXV thermal expansion valve

## Compressor

- 1 - 5-ton scroll compressor

## Heating and Cooling

Cooling capacity 62,000 BTUs - 5 tons  
 Heating capacity 60,000 BTUs - 12 kW

## Electrical

208/240 single phase / 60 HZ  
 Breakers and contactors for motor protection  
 Single stage heat - heat pump  
 RLA 34.1 amps  
 LRA 165 amps

## Blower

Single forward curved fan  
 2250 CFM

## Condenser Fans

Axial

## Heating Coil

Optional 5 kW / 10 kW

## Included

Remote temperature controller with 25' cable  
 30' power cable with plug end  
 14" diameter, 10' supply and return ducting  
 Foam-filled tires



